

This drawing, specifications, and concepts contained here in are the sole property of Dart Aerospace, and may not be reproduced or used in any fashion without the prior written permission of Dart Aerospace Eugene, OR.

		revisións			
REV	ECR	DESCRIPTION	DATE	INITIAL	APPROVED
1		RELEASED FOR PRODUCTION.	5/10/2016	DPD	JAG







NOTE: REF EUROCOPTER T/N: M631V3027101.





TORLON BUSH EXCHANGE

									DWG NO.	RB	FM6	31V30	27101 15
ASSY QTY	ASSY QTY	B/O	Part #	UNIT QTY	Description	Material	B/O INFORMATION OR SPECIFICATIONS	PG.	MAT'L HEAT			u	INLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES + .005 FRACTIONS ± 1/8
			-1	1	THREADED HALF	6061		2	TREAT FINISH			.xx	± .01 ANGLES ±.5° ± .1 SURFACES = 125/
			-3	1	COUNTERBORE HALF	6061		3	SPEC			1. BRE	AK ALL SHARP EDGES
		B/O	-5	1	SOCKET HEAD CAP SCREW	S.S.	M5 X 0.8mm X 18mm (MCMASTER-CARR #91292A127)	1	DRAWN BY: CHECKED:	DUERFE		2. DIME	x 45° OR .015R ENSIONAL LIMITS APPLY
		B/O	-7	1	воттом гоам	Y20 BLACK	2.97 X 5.93 X 8.43 (I.R. SPECIALTY)	4	OPPS APPR:	MACKO\ ANDERS		3. INTE	ER PLATING RPRET DIM AND TOL PER E Y14.5M-2009
		B/O	-9	1	TOP FOAM	Y20 BLACK	.72 X 5.93 X 8.43 (I.R. SPECIALTY)	5	QA APPR:	LINDSA		Aoiii	USED ON MODEL
		B/O	-11	1	CASE	PLASTIC	PELICAN #APP-1150-E	N/S	APPROVED:	GILBER	Γ		H175
		B/O		1	DART PLACARD	ALUMINUM	RB41011	N/S	SCALE	1:2	DATE	3/23/201	6 SHEET 1 OF 5

This drawing, specifications, and concepts contained here in are the sole property of Dart Aerospace, and may not be reproduced or used in any fashion without the prior written permission of Dart Aerospace Eugene, OR.

		REVISIONS			
REV	ECR	DESCRIPTION	DATE	INITIAL	APPROVED





## NOTES:

1. DUAL FINISH:

1ST: CLEAR ANODIZE
MIL-A-8625 TYPE II CLASS I.
2ND: POWDER COAT YELLOW, FED #13538.

2 NO POWDER COAT ON THIS SURFACE.



TORLON BUSH EXCHANGE

DWG NO.	RBE	M63	31 V	/30271	01-1 REY							
MAT'L 6061 HEAT TREAT					S OTHERWISE SPECIFIED NSIONS ARE IN INCHES FRACTIONS ± 1/8							
FINISH SEE N	NOTE 1			.XX ± .01	ANGLES ±.5° SURFACES = 125/							
SPEC				1. BREAK ALL SHARP EDGES								
DRAWN BY: DUERFELDT CHECKED: MACKOVJAK OPPS APPR: ANDERSON QA APPR: LINDSAY				.015 x 45° OR .015R								
			DIMENSIONAL LIMITS APPLY AFTER PLATING     INTERPRET DIM AND TOL PER ASME Y14.5M-2009  USED ON MODEL									
							APPROVED:	GILBER	Γ			H175
							SCALE	1:1	DATE	3/2	23/2016	SHEET 2 OF 5

